

# **Stock (SK) & Street (ST)**



## **Stock & Street 4x4 Category Rules**

### **Stock 4x4 (SK)**

#### **Weight Breaks**

5500 & 6500 lbs. Weight is with driver.

#### **REGULATIONS**

1. Must be as it came from the factory
2. Leveling/lift kits allowed (no stops)
3. Rim and tire modifications from stock allowed.
4. Muffler change allowed (must be a complete system)
5. Hitch must be Reese style receiver hitch in factory position and no more than 26" from the ground at hook point.

### **Street 4x4 (ST)**

#### **Weight Breaks**

4500, 5500, & 6500 lbs. Weight is with driver.

#### **REGULATIONS**

1. Must have factory or aftermarket bumper (no home built bumpers).
2. Must be street legal – working lights, signals, and mirrors (does not need to be registered).
3. Hood must be in place over engine compartment.
4. Must have working brakes on all 4 wheels.
5. Engine modifications allowed: 515 CID limit; Single carburetor, naturally aspirated, limited to 4150 base (no dominators).
6. Exhaust modifications: Open headers allowed; Exhaust must exit under the vehicle toward the rear.
7. Gasoline only.
8. No added weights.
9. Hitch must be Reese style receiver hitch in factory position and no more than 26" from the ground at hook point.
10. TIRES: D.O.T. tires only. No cut tires.
11. Suspension: no less than 2" of travel; any airbags must be deflated at tech time and while making pull.
12. No axles larger than Dana 70 series or 14 bolt or stock (no military, Rockwell etc.).
13. Steering: Must be factory steering; OEM replacement power steering allowed.

14. Fuel tanks must be bolted down.
15. Bed floor must be complete.
16. Manual or automatic transmission. No racing transmissions.
17. No quick change or homemade transfer cases.
18. Must have bench seat or no less than 2 individual seats.
19. Must have a minimum 2 Lb. fire extinguisher mounted in cab within reach of the driver.
20. Push bars allowed:
  - a. Height: no higher than hood
  - b. Width: no more than 2" wider than frame rails
  - c. Clearance: Minimum 12" from the ground
  - d. Protrusion: Maximum 16" from furthest point of the grill
  - e. Front bumper must be in place.
21. Must have OEM motor mounts in stock location.

